


ELEMENTOS DE MANIOBRA

CONTROL ELEMENTS • ÉLÉMENTS DE MANŒUVRE • ELEMENTOS DE MANOBRA



Empuñadura graduable hembra

Female indexed clamping handle

Poignée débrayable taraudée

Punho graduável fêmea

M

Zamak, epoxy negro

Die cast zinc, black powder coated

Zamak (zinc injecté) époxy noir

Zamak, epóxi preto

Material del inserto: Acero pavonado

Insert material: Black-oxide treated steel

Insert: Taraudage en acier oxydation noire

Material do inserto: Aço de oxidação negra

ES EN FR PT

P Gama preferida

Preferred range
Gamme préférence
Gama preferida

Gama estándar

Standard range
Gamme standard
Gama padrão

Temperatura de uso -30°C / +200°C

Working temperature
Température d'emploi
Temperaturas de utilização

	Ref.		M	A	B	C	D
	EGZ-43-4-N	●	M4	43	30	10	30
	EGZ-43-5-N	●	M5	43	30	10	30
P	EGZ-43-6-N	●	M6	43	30	10	30
	EGZ-65-6-N	●	M6	65	34	14	45
P	EGZ-65-8-N	●	M8	65	34	14	45
	EGZ-65-10-N	●	M10	65	34	14	45
	EGZ-80-8-N	●	M8	80	42	16	57
P	EGZ-80-10-N	●	M10	80	42	16	57
P	EGZ-80-12-N	●	M12	80	42	16	57
	EGZ-94-12-N	●	M12	94	50	20	65
P	EGZ-94-14-N	●	M14	94	50	20	65
	EGZ-94-16-N	●	M16	94	50	20	65
	EGZ-108-14-N	●	M14	108	56	23	75
P	EGZ-108-16-N	●	M16	108	56	23	75
	EGZ-108-18-N	●	M18	108	56	23	75



Otros colores de empuñaduras bajo consulta.

Other handle colors are available by request.

Autres couleurs sur demande.

Outras cores de punho, disponíveis sob consulta.

